## Specification

Parts Counter

Small size

## MINK-S

Control No.

Reference No. NT20141210-03

[A] Prepared on December 10, 2014
[B] Revised on September 25, 2015
[C] Revised on January 18, 2018
[D]



parts. (W) × 254.5 mm (L) × 184 mm (H) mately 0.9 liters ple Approximately 290 bolts of M6 × 15 mm with washer IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII
nately 0.9 liters ble Approximately 290 bolts of M6 × 15 mm with washer Interview of M6 × 15 mm with washer
ble Approximately 290 bolts of M6 × 15 mm with washer Image: Second Se Second Second Se
ble Approximately 290 bolts of M6 × 15 mm with washer Image: Second Se Second Second Se
ble Approximately 290 bolts of M6 × 15 mm with washer Image: Second Se Second Second Se
Take-out check sensor equipped
Pan height: 89 mm (from the bottom surface)
6 bolts (with washer, flange)
shers, etc.
eces other than those listed above may be used with this device.
provide us with actual workpieces that you are considering to use.
0 seconds/15 pieces
actual example 5 pieces/20 to 30 seconds (M6 $\times$ 20)
*Depending on workpiece conditions
Stainless steel
plate Industrial resin
upply : DC 24 V / 1 A
*AC-DC Adapter AC 100-240V 50/60Hz 0.6A
m 15 pieces